

## 'Camlock' product range extended

Since 2016, Elaflex has supplied '**Camlock' Couplings from its own production** – guaranteed to EN 14420-7 standard in every regard, reliable and operationally safe. Male adapters and female couplers with female BSP thread or integrated hose tail have so far been available in DN 19-100, made of stainless steel.

This product range has been extended. In the second quarter of 2017 **all versions in the new quality will be also deliverable in brass.**

**Dust plugs AVB and caps AMB in aluminium** will be provided end of the year.

Available from autumn **type 'EASYLOC'**. These female couplers with additional lever lock will be supplied in DN 19-50, made of stainless steel. The lever lock avoids an unwanted disconnection of the lever during operation, e.g. due to pulsation or vibration.

The new range of cam locking couplings from own production is the Elaflex answer to the market trend towards ever worsening qualities. They fulfill the standard and have improved product properties compared to similar couplings on the market.

### Advantages of original Elaflex 'Camlock' couplings:

- Wall thickness and tolerances to standard
- Material specification to standard (stainless steel, aluminium, brass)
- Inspection test certificates EN 10204 - 3.1 available on request
- Machined inner surfaces < Ra 1,6
- Ergonomic, contour shaped levers, optimised lever geometry for improved coupling safety
- Robust lever attachment
- Pressure resistant: PN 16 bar for all materials, with a high safety factor
- Manufacturer's liability: clear Elaflex and batch marking for traceability
- Easy attachment with standardised hook spanner or open-end wrench

For further information, please visit our website:  
[www.elaflex.de/en/camlock](http://www.elaflex.de/en/camlock)



Type 'EASYLOC'  
with lockable levers

ELAFLEX - Gummi Ehlers GmbH  
Marketing Karsten Ehlers  
Tel. +49 40-540 005-0  
E-Mail [info@elaflex.de](mailto:info@elaflex.de)  
Internet [www.elaflex.de](http://www.elaflex.de)