

Dry Hose Delivery Nozzles 'ZL' of Stainless Steel

When distributing fluids large quantities are commonly purchased and then filled in small quantities such as drums and IBC (Intermediate Bulk Containers).

For this open media transfer Elaflex supplies a **new version** of **dry hose delivery nozzles 'ZL'**.

The **ball valve construction** is **made of stainless steel** and **PTFE seals**. It is suitable for universal applications in the chemical and petroleum industry.

A full bore of DN 50 enables flow rates of approx. 50 – 900 litres/minute, max. working pressure 10 bar.

In addition to the **standard type 'ZL' with 2" or 3" BSP thread**, other hose side connections of stainless steel in DN 50 und 80 are available:

- with 'TW' male adapters **VK**
- with 'Camlock' adapters **AVKI**
- with **Dry Disconnect Couplings DDC-V**

For an improved handling it is possible to use a swivel of stainless steel (type DG) between nozzle and hose assembly.

All technical details – Download:

[CatPage 535](#) and [Elaflex Information 8.19](#)

All 'ZL' types can also be configured online:

nozzleconfigurator.elaflex.de

(1063 characters)

Elaflex is a specialist company in safe connections for the handling of hazardous goods and sensitive fluids. We have extended our comprehensive product range of hoses, fittings and couplings by the new dry hose delivery nozzles to address manufacturers of (petrol) chemicals and pharmaceuticals as well as chemical distributors.

