

# What you see is what you get.

<http://>

[nozzleconfigurator.  
elaflex.de](http://nozzleconfigurator.elaflex.de)



**ELAFLEX**

→ Select by Application

Type

**ZVA Slimline 2**  
Automatic nozzle DN 19,  
max. flowrate 80 l/min.  
For all standard fuels -  
also with ethanol  
content- and Biodiesel.  
Petrol Station Aircraft  
refuelling versions.

**ZVA Slimline 2 GR**  
Automatic nozzle for  
active vapour recovery,  
max. flowrate 45 l/min.  
For all standard gasoline  
fuels also with ethanol  
content.

**ZVA Slimline AdBlue**  
Automatic nozzle DN 15,  
max. flowrate 40 l/min.  
For 'AdBlue' urea  
solution (DEF/AUS 32/  
AFLA 32). Spout with  
magnet opening to avoid  
misfilling.

**ZVA Slimline for  
special media**  
Automatic nozzles DN 19,  
max. flowrate 60 l/min.  
Gunmetal, bronze,  
stainless steel or  
aluminium types with  
special seals.

ZVA 25

Petrol Station  
Automatic  
Diesel/ Gasoline

Petrol Station  
Automatic  
AdBlue

High Flow  
Automatic  
Diesel/ Gasoline

Low/Medium Flow  
Manual  
Diesel/ Gasoline / Oil

High Flow  
Manual  
Diesel/ Gasoline / Oil

Automatic  
Special Media

Automatic  
Aircraft Refuelling

Manual  
Aircraft Refuelling

Standard  
LPG

## now for all nozzles

**Select - Configure - Enquire  
Nozzles for:**

- Petrol Stations
- Commercial Refuelling
- AdBlue
- LPG Autogas
- Fuel Oils
- Aviation
- Chemicals
- Solvents

**ELAFLEX**

ELAFLEX HIBY Tanktechnik GmbH & Co. KG  
[www.elaflex.de/english](http://www.elaflex.de/english) · [info@elaflex.de](mailto:info@elaflex.de)